

Energy Efficient Texas Hurricane Resistant Openings




Energy Efficient and Hurricane Rated

The Ceco Trio-E door meets Texas Department of Insurance (TDI) most stringent code requirements for hurricane force winds and flying debris up to +/-70. Plus, Trio-E helps increase a building's thermal efficiency and reduce energy loss. Energy is a major cost for building owners. The Trio-E door can provide significant energy savings on new or retrofit projects while helping to protect the owner's investment from severe weather.



Ceco Door
9159 Telecom Drive • Milan, TN 38358
Tel (888) 232-6366 • Fax (888) 232-6462
archhelp@cecodoor.com
www.cecodoor.com



Experience a safer
and more open world

Ceco is a brand associated with AADG, Inc., an ASSA ABLOY Group company. Copyright © 2020, AADG, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of AADG, Inc. is prohibited.

CEC-167-02/20

Strong

- Hurricane rated up to +/- 70 psf
- Single in swing 3'0" x 7'0" openings hardware:
 - Corbin Russwin ML2000, ML20600, ML20900 Series mortise locks with latch bolt and dead bolt
 - SARGENT 11 Line Series cylindrical locks
 - SARGENT 7800, 8200, R8200 Series mortise locks with latch bolt and dead bolt
- Single out swing 3'0" x 7'0" opening hardware:
 - Yale 7150 and 7250 Series exit device
- Pair in swing 6'0" x 7'0" openings

Active leaf:

- Corbin Russwin ML2000, ML20600, ML20900 Series mortise locks with latch bolt and dead bolt
- SARGENT 7800, 8200, R8200 Series mortise locks with latch bolt and dead bolt

Inactive leaf:

- Rockwood 556 WS Series flush bolts

- Steel stiffened core adds strength, durability and security to any building

Beautiful

- No vertical weld marks on door face sheets for a blemish free surface
- Factory Finish available with standard and custom colors to choose from

Green

- Energy Efficient opening (U-Value 0.38*) significantly reduces cooling and heating costs
- First steel stiffened hollow metal swinging door to qualify for GreenGuard Gold

* U-Value of 0.38 achieved when installed in Ceco Kerf frame