# StormPro® Multi-Point Exit Tornado Resistant Assembly UL Classified to ICC500 - 2014





Ceco Door StormPro® Multi-Point Exit assemblies include glazed and flush paired openings 6'0" x 6'8" minimum through 8'0" x 8'0" maximum with a required mullion. Single glazed and flush openings are available from 3'0" x 6'8" minimum to 4'0" x 8"0" maximum. These StormPro® assemblies give end-users another option for creating highly functional safe rooms with easy means of egress.

The StormPro® Multi-Point Exit assembly helps shield occupants in a safe room from flying debris. The assemblies are UL classified to ICC-500 2014 and comply with FEMA P320 and P361. StormPro® doors are also fire rated up to and including 3 hours. As with all StormPro® products, the third party Underwriters Laboratory certification labels are applied to each assembly.

Ceco Door 9159 Telecom Drive • Milan, TN 38358 Tel (888) 232-6366 • Fax (888) 232-6462 archhelp@cecodoor.com www.cecodoor.com

Experience a safer and more open world

### **Available Sizes:**

- Pairs 6'0" x 6'8" minimum to 8'0" x 8'0" maximum
- Singles 3'0" x 6'8" minimum to 4'0" x 8'0" maximum

## Frame Type:

- StormPro 14 gauge frame single, 4" depth thru 14"
  StormPro 14 gauge frame pairs, 5-1/2" depth thru 14"
- 4" head option
- Masonry or EO anchors

## Door Type:

 14 gauge StormPro door with polystyrene core (Honeycomb core if fire rated)

# **Optional Glazing:**

- Single 10"x10" visible glass factory installed with kit located at 60" above door bottom to centerline of glass
- 90 minute UL fire rating available

# **Hardware Options:**

- Multi-Point Exit Device: Corbin Russwin FE5400S
- Hardware Mullion: Corbin Russwin FE707A Series or FE708A Series

#### Hinges:

- Mckinney SP BUTT HINGES
- MARKAR HG305, HG305WT10, FM300, FM300WT and other continuous hinges

#### **Accessories:**

 Door closers, perimeter seals, electronic power transfer, door position switches, holders/stops, viewers, rod guards and kick plates are also available

**Note:** Other hinges and accessories available, see tech manual.