

StormPro® Surface Vertical Rod Exit Tornado Resistant Assembly UL Classified to ICC500 - 2014



NEW
Glazing
Available



Ceco Door StormPro® Surface Vertical Rod Exit assemblies include flush and glazed paired openings 6'0" x 6'8" minimum through 8'0" x 8'0" maximum without a required mullion. Single flush and glazed openings are available from 3'0" x 6'8" minimum to 4'0" x 8'0" maximum. These StormPro® assemblies give end-users another option for creating highly functional safe rooms with easy means of egress.

The StormPro® Surface Vertical Rod Exit assembly helps shield occupants in a safe room from flying debris. The assemblies are UL classified to ICC-500 2014 and comply with FEMA P320 and P361. StormPro® doors are also fire rated up to and including 3 hours. As with all StormPro® products, the third party Underwriters Laboratory certification labels are applied to each assembly.

Ceco Door
9159 Telecom Drive • Milan, TN 38358
Tel (888) 232-6366 • Fax (888) 232-6462
archhelp@cecodoor.com
www.cecodoor.com

Experience a safer
and more open world

Available Sizes:

- Pairs 6'0" x 6'8" minimum to 8'0" x 8'0" maximum
- Singles 3'0" x 6'8" minimum to 4'0" x 8'0" maximum

Frame Type:

- StormPro 14 gauge frame, 5-3/4" depth thru 14"
- 4" head option
- Masonry or EO anchors

Door Type:

- 14 gauge StormPro door with with polystyrene core (Honeycomb core if fire rated)

Optional Glazing:

- Single 10"x10" visible glass factory installed with kit located at 60" above door bottom to centerline of glass
- 90 minute UL fire rating available

Hardware Options:

- Surface Vertical Rod Exit Device: SARGENT FM8700 (mullion optional)

Hinges:

- MCKINNEY SP BUTT HINGES
- MARKAR HG305, HG305WT10, FM300, FM300WT and other continuous hinges

Accessories:

- Door closers, perimeter seals, electronic power transfer, door position switches, holders/stops, viewers, rod guards and kick plates are also available

Note: Other hinges and accessories available, see tech manual.