REV	DESCRIPTION	DATE	ENGINEER





DETAIL A



ISO VIEW

DETAIL B



ISO VIEW

SLAB MOUNT OPTION (SLAB SIZE VARIES)
FOR THE SLAB MOUNTED TRUCK ASSEMBLIES,
USE ½" DIAMETER HILTI HIT-HY 200 + HAS W/ 6" MIN. EMBED OR EQUIVALENT,
IN 3000 PSI CONCRETE REINFORCED PER ACI 301



SIDE VIEW



FRONT VIEW

DETAIL C: POST MOUNT OPTION



FRONT VIEW SIDE VIEW TOP VIEW

DETAIL D: TOP POST MOUNT



FRONT VIEW SIDE VIEW TOP VIEW

NOTICE TO PERSONS RECEIVING THIS DRAWING AND/OR TECHNICAL INFORMATION
Ameristar Perimeter Security USA Inc claims proprietary rights to the material disclosed hereon. This drawing and/or technical information is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown or referred to hereon without direct written permission from Ameristar Perimeter Security USA Inc to the user. This drawing an /or technical information is the property of Ameristar Perimeter Security USA Inc and is loaned for mutual assistance to be returned when its purpose has been served.

UNLESS OTHERWISE SPECIFIED TOLERANCES

X.X	± .06
X.XX	± .03
X.XXX	± .02
ANGLES	± 0.5°
FRACTIONS	± 1/8
SURFACE FINISH	63

DRAWING COMPLIES WITH ASME Y14.5M - 1994
INCH
MM
THIRD ANGLE PROJECTION

MATERIAL: SEE BOM
HEAT TREATMENT
SURFACE/FINISH
MASS | VOLUME | SURFACE AREA

ASSA ABLOY
Ameristar Perimeter Security USA Inc
Tulsa

TT-IS CNT TRI 2R FLB 4" GAP ARCHITECTURAL DRAWING

DATE CREATED	DRAWN BY	DESIGNED BY
11/4/2021	nathan	nathan

DOCUMENT ID	SCALE	SIZE
	1:28	B

DRAWING NUMBER (ALT ID)
TT-IS CNT TRI 2R FLB 4 IN GAP ARCH DRAWING

CONFIGURATION Default
LEGACY ID

Out to Out									
	6'-8'	8'-10'	10'-12'	12'-14'	14'-16'	16'-18'	18'-20'	20'-22'	22'-24'
6'H	128.5	164.5	194.5	212.5	242.5	272.5	290.5	326.5	380.5
7'H	128.5	164.5	182.5	212.5	254.5	266.5	290.5	326.5	362.5
8'H	122.5	158.5	182.5	218.5	236.5	266.5	290.5	338.5	362.5
9'H	134.5	158.5	182.5	218.5	236.5	266.5	314.5	338.5	362.5
10'H	134.5	158.5	182.5	218.5	236.5	266.5	314.5	338.5	392.5

Post Centers									
	6'-8'	8'-10'	10'-12'	12'-14'	14'-16'	16'-18'	18'-20'	20'-22'	22'-24'
6'H	12.25	22.75	28.75	22.75	28.75	34.75	28.75	40.75	70.75
7'H	12.25	22.75	16.75	22.75	40.75	28.75	28.75	40.75	52.75
8'H	12.25	16.75	16.75	28.75	22.75	28.75	28.75	52.75	52.75
9'H	16.75	16.75	16.75	28.75	22.75	28.75	52.75	52.75	52.75
10'H	16.75	16.75	16.75	28.75	22.75	28.75	52.75	52.75	82.75

UNLESS OTHERWISE SPECIFIED TOLERANCES
X.X ± .06
X.XX ± .03
X.XXX ± .02
ANGLES ± 0.5°
FRACTIONS ± 1/8
SURFACE FINISH 63

DRAWING COMPLIES WITH ASME Y14.5M - 1994
INCH
MM
THIRD ANGLE PROJECTION

MATERIAL: SEE BOM
HEAT TREATMENT
SURFACE/FINISH
MASS | VOLUME | SURFACE AREA

ASSA ABLOY
Ameristar Perimeter Security USA Inc
Tulsa

TT-IS CNT TRI 2R FLB 4" GAP ARCHITECTURAL DRAWING

DATE CREATED: 11/4/2021
DRAWN BY: nathan
DESIGNED BY: nathan
DOCUMENT ID
SCALE: 1:96
SIZE: B
DRAWING NUMBER (ALT ID): ***TT-IS CNT TRI 2R FLB 4 IN GAP ARCH DRAWING***

CONFIGURATION Default
LEGACY ID
SHEET **2** OF **2**