

Completely constructed from glass with only the most minimal stainless steel frame and cappings, the Crystal TQ is the most transparent revolving door available. Despite its transparency however, it makes a striking entry to any building. This manual revolving door is available with three or four door wings.






Dimensions and Specifications

Α			В	С	D	E
Diameter	Capacity	# of Door	Instal-	Throat	Height	Glass
	/ Minute	Wings	lation	Opening	Under	Ceiling
			Width		Ceiling	Thickness
6′ 6″	2x 20-25	4	6′ 8″	4' 5-1/2"	7′ 0″-8′ 6″	11/16"
7′ 0″	2x 20-25	3	7′ 2″	3′ 4″	7′ 0″-8′ 6″	11/16"
7′ 0″	2x 20-25	4	7′ 2″	4' 10-1/8"	7′ 0″-8′ 6″	11/16"
7′ 6″	2x 20-25	3	7′ 8″	3' 6-3/4"	7′ 0″-8′ 6″	11/16"
7′ 6″	2x 20-25	4	7′ 8″	5′ 2″	7′ 0″-8′ 6″	11/16"

^{*}For doors with a diameter of 7'6" and greater, please consult with our design experts







Features and Options

Characteristics	Standard	Option
Manual operation	•	
Collapsible door set	•	
1/2" tempered glass door set	•	
Floor frame / matwell ring	•	
Speed control	•	
Stainless steel #4 brushed finish	•	
Polished stainless steel trim (#8)		•
Low iron glass		•
Electric winglocking		•
Herculite-style door wings		•

Emergency Egress

The Crystal TQ is equipped with door wings that can be manually collapsed during an emergency. (Escape route requirements are subject to local regulations.)

Technical Specifications

Power Supply: 110 VAC, 50/60 Hz*

Power Consumption							
Stationary:	85W						
Ambient Temperature:	-1°E to ±122°E						

*With electric winglocking option deployed