APPENDIX D – CERTIFICATION LETTER:

4455 Genesee Street, Buffalo, New York 14225 | Phone: 716.632.7500 | Fax: 716.631.6969 | www.calspan.com



January 6, 2017

Test Report: TR2974

To whom it may concern:

This letter is to certify that the subject barrier, the G-Force Post and Beam, provided by Gibraltar, was tested to the requirements of the ASTM standard F-2656-07, Standard Test Method for Vehicle Crash Testing of Perimeter Barriers, in place when the test was performed.

The test was performed at Calspan Corporation on December 20th, 2016. The barrier was impacted by a truck weighing 6921.9 kg (15,260 lbs.) travelling at 50.40 mph (81.11 kph). Post-test measurements of the dynamic position of the test vehicle's payload (truck bed) with respect to the trailing edge of the barrier show that the left and right leading edge of the truck bed was stopped at 828mm and 871mm, respectively. As such, based on the truck mass, impact velocity and penetration into the protected zone, the barrier rating per the ASTM standard F-2656-07 is M50-P1.

Calspan is accredited to ISO 17025:2005 to perform ASTM F2656-07 testing by Perry Johnson Laboratories Accreditation, Inc. (PJLA) under Certificate Number L13-137 and Accreditation Number 76654.

Respectfully,

Edward Dutton Test Director

Edward Dutton

Safer Highways...Safer Skies

Aerospace Sciences | Crash Research | Flight Research | Transportation Research