



TEST No.: BR0132  
Test Standard: ASTM F3016-19  
Company: SBI Industrial  
Model: 4.5" Round Pipe with I-Beam Stiffener  
Product Rating: P2

9/1/22

To whom it may concern:

This letter is to certify that the 4.5" Round Pipe with I-Beam Stiffener provided by SBI Industrial was tested to the requirements of the ASTM standard F3016-19. This was the standardized test method for low speed (30mph and lower) dynamic crash testing using a surrogate test vehicle for perimeter barrier crash testing at the time the test was performed.

Testing was performed at the Calspan Corporation, on September 1, 2022. The 4.5" Round Pipe with I-Beam Stiffener was impacted by a surrogate test vehicle (STV) weighing 2274.5 kg (5014.4 lbs.) travelling at 21.8 mph [35.1 kph]. Post-test measurements of the maximum dynamic penetration into the protected area as measured from the reference line of the test article, found the surrogate test vehicle to have the greatest intrusion. The surrogate test vehicle was measured as having a maximum intrusion of 20.5" [520.7mm] behind the trailing edge (reference line) of the impacted test article. As such, based on the surrogate test vehicle's mass, impact velocity and measured penetration into the protected area, the test article was given a penetration rating P2 as allowed by the standard

Calspan is accredited to ISO/IEC 17025:2017 to perform ASTM F3016-19 testing by Perry Johnson Laboratories Accreditation, Inc. (PJLA) under Certificate Number L20-602-R1 and Accreditation Number 76654.

Respectfully,

A handwritten signature in blue ink that reads "David Casey".

David Casey  
Test Director  
Calspan Barrier Test  
716.631.4105  
David.casey@calspan.com

*Safer Highways...Safer Skies*