



# AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

**Applicant:** Hy-Security Gate Inc.  
**Address:** 6623 S. 228th Street  
Kent, WA 98032, USA  
**Country:** USA  
**Contact:** Mr. Brian Knerr  
**Phone:** (800) 321-9947  
**FAX:** (888) 321-9946  
**Email:** bknerr@hysecurity.com

**Manufacturer:** Hy-Security Gate Inc.  
**Address:** 6623 S. 228th Street  
Kent, WA 98032, USA  
**Country:** USA  
**Contact:** Mr. Brian Knerr  
**Phone:** (800) 321-9947  
**FAX:** (888) 321-9946  
**Email:** bknerr@hysecurity.com

**Party Authorized To Apply Mark:** Same as Manufacturer  
**Report Issuing Office:** Dallas, TX

**Control Number:** 2003349

**Authorized by:** *Edward Kelley*  
for Dean Davidson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.  
545 East Algonquin Road, Arlington Heights, IL 60005  
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

|                     |   |
|---------------------|---|
| <b>Standard(s):</b> | UL 325 Issued: 2013/10/14 Ed: 6 Door, Drapery, Gate, Louver, and Window Operators and Systems - Effective Date: 1/12/2016 &             |
|                     | CSA C22.2 No. 247, 2nd Edition issued: 2014/07/01, Rev: Errata 2015/06/01 Operators and Systems of Doors, Gates, Draperies, and Louvers |
| <b>Product:</b>     | Gate Operators  |



## AUTHORIZATION TO MARK

Sliding Gate Operator Series 111-x ST, 222-x ST, 333-x ST and 444-x ST, whereas x is a letter or a combination of letters representing various AC or DC motors, HP ratings, speeds and pull force rating.  
Sliding Gate Operator Series 222 X2 ST (50VF2), 222 X3 ST (50VF3), whereas X is a letter or a combination of letters representing various AC or DC motors, HP ratings, speeds and pull force rating.

Swinging Gate Operator Series HRG-220-x ST and HRG-222-x ST, where x is a letter or a combination of letters representing various AC or DC motors, HP ratings, speeds and Gate weights in Pounds.

Swing Gate Operators, Models SwingSmart DC20, and SwingSmart DCS 20, HydraSwing 40F, HydraSwing 40, HydraSwing 40 Twin, HydraSwing 80F, HydraSwing 150

**Models:**

Vertical Lift Gate Operator Series HVG-420-x ST and HVG-460-x ST, where x is a letter or a combination of letters representing various AC or DC motors, HP ratings, speeds and Gate weight in Pounds.

Barrier Arm Gate Operator Series HTG-320-x ST, where x is a letter/number or a combination of letters and numbers representing various AC or DC motors, HP ratings and arm length capacity in Feet.

Horizontal Slid-Gate Operators, Models SlideWinder 24, SlideWinder 24S, SlideWinder 24F, SlideWinder 24FS, SlideWinder 24VF, SlideWinder 24VFS, SlideWinder 38, SlideWinder 38S, SlideWinder 38F, SlideWinder 38FS, SlideWinder 38VF, SlideWinder 38VFS., SlideSmart DC 10F, SlideSmart DC 10FW, SlideSmart DCS 10F, SlideSmart DCS 10FW, SlideSmart DC 15, SlideSmart DC 15W, SlideSmart DCS 15, and SlideSmart DCS 15W.