



## WALLACE PERIMETER SECURITY CANTILEVER SLIDING GATE

Cantilever sliding gates provide a secure solution for a variety of different applications. Cantilever sliding gates do not rely on any surface mounted rail or track, therefore ease of operation and maintenance is dramatically improved. No ground track also means that the gate can accommodate heavy traffic in continuous duty applications.

Modular construction allows for quick, economical delivery and cost effective future serviceability.

The rack and pinion drive is quiet, and provides a secure entrance while maximizing the life of the gate. Sealed bearings in the rollers and nylon polyamide rack and pinion gears eliminate the maintenance requirements associated with conventional chain drive operators. Straight forward sizing allows for quick shipping.

## ALPHA CANTILEVER SLIDING GATE

The Alpha gate combines optimum quality and security. Strong and clever, this smoothly running gate is available with a variety of infill options, including chain-link and welded wire.








## **DELTA**


## **CANTILEVER SLIDING GATE**


The contemporary design of the Delta gate is sturdy and safe with no **diagonal braces** that intruders could use to climb over. The vertical bar infill is available in a variety of colors complementing the appeal of your property.




| WALLACE PERIMETER SECURITY SLIDING GATES |  |                        |               |              |                                    |  |   |  |
|--|--|------------------------|---------------|--------------|------------------------------------|--|---|--|
|  | Features   | Infill<br>Options      | Max<br>Height | Max<br>Width | Opening<br>Speed                   | Finish   | Power<br>Requirements   | Applications   |
| Alpha Gate                               | <ul> <li>Rack and pinion drive</li> <li>Concealed nylon rollers</li> <li>Anti-climb top rail</li> </ul>  | Chain link Welded wire | 8'            | 30'          | • 1' per second<br>• 2' per second | Hot dip galvanized/<br>mill 1 finish aluminum<br>• Powder coat options | Voltage     115 -230 V     Frequency     50-60 HZ     Current     15 AMP     dedicated     circuits | <ul> <li>Airports</li> <li>Seaports</li> <li>Commercial facilities</li> <li>Water treatment<br/>facilities</li> <li>Public transportation</li> </ul> |
| Delta Gate                               | <ul> <li>Rack and pinion drive</li> <li>Concealed nylon rollers</li> <li>Anti-climb top rail</li> <li>Matches ornamental fence line *</li> </ul> | •Vertical<br>picket    | 8'            | 30'          | • 1' per second<br>• 2' per second | Hot dip galvanized • Powder coat options                               | Voltage 115 -230 V Frequency 50-60 HZ Current 15 AMP dedicated circuits                             | • Same applications as the Alpha Gate  |









\*Screen must be installed to be compliant with ASTM Standards/UL Standards.

**Listed to UL 325** (class 1,2,3 &4)



90 Lowson Crescent Winnipeg, Manitoba Canada R3P 2H8 Phone: 866.300.1110

Fax: 204.284.1868

wallaceperimetersecurity.com